

# Halo Plus

Uniquely Profiled Surface/ Suspended Downlighter

Creating ambience  
with a difference



## What makes Halo Plus different?



### Aesthetics :

- Compact and trendy design
- Deep inset diffuser to maintain low UGR
- Tapered profile housing with micro texture powder coating
- Aesthetically integrated suspension and power cable in suspended version



### Performance:

- Best in class LED with efficacy upto 100 Lm/W and THD<10%



### Choice:

- Option available in color: Matte Black & White
- Mounting options: Surface & Suspended

Unique product on aesthetics and performance, ideal for enriching ambience in open ceiling work spaces.

Part of inSync™ range offering human centric lighting.

\*12W / 15W only

**IoL**™  
Internet of Lighting

# Halo Plus

Uniquely Profiled Surface/ Suspended Downlighter


## Specifications

- HET PMMA diffusers provide high transmittivity
- Tapered design blends well with the architecture
- CRCA powder coated housing, available in both black and white colour options
- In compliance to IS 10322 part 5/ Sec1 1987

## Installation

Ideal for surface / suspended mounted application.  
1.5 meter suspension cable is provided along with the product.

## Dimensions Drawing



## Electrical Data

IP20

Catalogue No.	Power (W) ±10%	Rated Voltage (VAC)	Input current (Amp)	Case Lot (In No's)
LD99-151-XXX57SMWH	12	240	0.052	12
LD99-151-XXX40SMWH	12	240	0.052	12
LD99-211-XXX57SMWH	15	240	0.065	12
LD99-211-XXX40SMWH	15	240	0.065	12
LD99-281-XXX57SMWH	18	240	0.080	12
LD99-281-XXX40SMWH	18	240	0.080	12
LD99-151-XXX57SMBL	12	240	0.052	12
LD99-151-XXX40SMBL	12	240	0.052	12
LD99-211-XXX57SMBL	15	240	0.065	12
LD99-211-XXX40SMBL	15	240	0.065	12
LD99-281-XXX57SMBL	18	240	0.080	12
LD99-281-XXX40SMBL	18	240	0.080	12
LD99-151-XXX57PMWH	12	240	0.052	12
LD99-151-XXX40PMWH	12	240	0.052	12
LD99-211-XXX57PMWH	15	240	0.065	12
LD99-211-XXX40PMWH	15	240	0.065	12
LD99-281-XXX57PMWH	18	240	0.080	12
LD99-281-XXX40PMWH	18	240	0.080	12
LD99-151-XXX57PMBL	12	240	0.052	12
LD99-151-XXX40PMBL	12	240	0.052	12
LD99-211-XXX57PMBL	15	240	0.065	12
LD99-211-XXX40PMBL	15	240	0.065	12
LD99-281-XXX57PMBL	18	240	0.080	12
LD99-281-XXX40PMBL	18	240	0.080	12


40 - Stands for 4000K  
57 - Stands for 5700K  
PM - Stands for Pendant mounted

WH - Stands for White housing  
BL - Stands for Black housing  
SM - Surface mounted

Also available in DALI/ Analog and white color tunable



## Applications



### Business Office:

Wipro Lighting, 5th floor, Godrej Eternia - C, Old Pune-Mumbai Highway, Shivajinagar, Pune - 411 005, India.  
Tel.: 020-6609 8700  
Fax: 020-6609 8777  
E-mail: helpdesk.lighting@wipro.com

### Registered Office:

Wipro Enterprises (P) Limited, 'C' Block, CCLG Division, Doddakannelli, Sarjapur Road, Bangalore 560 035, India.

Toll-Free No.: 1800-425-1969

www.wiprolighting.com

Follow us on [in](#) [t](#) [f](#) [i](#)

Innovation and improvement are a way of life at Wipro.

All rights reserved. Reproduction of this data in part or in whole without permission is prohibited. Care has been taken to ensure that the information content within is correct. We reserve the right to modify the product without prior intimation. Imitation of Registered Designs is a punishable offence.